# HyperGain<sup>®</sup> HG2415G 2.4 GHz Mini 15 dBi Reflector Grid Antenna

#### **Superior Performance**

The HyperGain<sup>®</sup> HG2415G Mini-Reflector Grid Antenna provides 15 dBi gain with a 19° beam-width for directional applications. Its compact design makes it nearly invisible in most installations, and it can be installed for either vertical or horizontal polarization. The antenna's heavy-duty tilt mount allows installation at various degrees of incline for easy alignment.



#### **Rugged and Weather-Proof**

This antenna's construction features a welded steel reflector grid for superior strength. The grid surface is UV powder coated for durability and aesthetics, and the open-frame design minimizes wind loading.

### **Electrical Specifications**


Frequency	2400 - 2500 MHz
Gain	15 dBi
-3 dB Beam Width	19°
<b>Cross Polarization Rejection</b>	> 20 dB
Front to Back Ratio	20 dB nom.
Impedance	50 Ohm
Max. Input Power	50 Watts
VSWR	< 1.5:1 avg.

#### **Mechanical Specifications**

Weight	2.6 lbs (1.18 kg)
Grid Dimensions	11.5 in. (29.2 cm) x 14 in. (35.56 cm)
Grid Material	Galvanized Welded Steel
Grid Finish	Light Gray UV Powdercoat
Mounting	1.0" (25mm) - 2.5" (60mm) diameter mast
Elevation Angle	0° to +15°
Operating Temperature	-45° C to +85° C

## **Wind Loading Data**

Wind Speed	100 MPH	140 MPH	100 MPH with ½" radial ice
Loading	8.2 lbs	16.1 lbs	33.2 lbs





#### **Available Connectors**

This antenna is supplied with a 24" pigtail with any of the connectors listed in the tables below. Specify the desired connector by choosing the appropriate part number.

#### **Standard Connectors**

The following standard connectors are available from stock:

Connector Type	Part Number	
N Female	HG2415G-NF	
N Male	HG2415G-NM	

# **Special Order Connectors**

This antenna is also available with the any of the following connectors by special order at a nominal additional charge. If you do not see your connector listed please contact our sales department.

Connector Type	Part Number
Reverse Polarity TNC Female	HG2415G-RTF
Reverse Polarity SMA Female	HG2415G-RSF
Reverse Polarity BNC Female	HG2415G-RBF
Reverse Polarity N Female	HG2415G-RNF
TNC Male	HG2415G-TM
SMA Male	HG2415G-SM
SMA Female	HG2415G-SF
BNC Male	HG2415G-BM

### **Guaranteed Quality**

All HyperGain® antennas are tested and backed by Hyperlink's One Year Warranty.

